

ÖLFLEX® FD 90 CY

DB 00266521
valid from: 14.12.2012**Application**

ÖLFLEX® FD 90 CY are **DESINA®** compliant screened, high-flexible sheathed cables designed for the European, North American and Canadian market, for flexible use and fixed installation, under light and medium mechanical load conditions. The PVC sheath is increased oil resistant. They are among others designed for use in dry and humid rooms. Outdoor use: They may only be installed with UV-protection and considering the temperature range. Usage of these cables in moving cable carriers or on motor drum guidance or under a tensile strain of more than 15 N/mm² is not allowed. The screen is a protection against electrical interference.

Application range:

In machine tools or for internal wiring in industrial machines etc.

USE acc. to UL: PVC sheathed cable for external wiring or internal wiring of electric and electronic equipment.

USE acc. to CSA: Cables for internal wiring or external wiring with or without mechanical stresses.

Design

Approvals	UL AWM Style 10107 (File No. E63634) ≥150 mm ² cUL AWM I A/B, II A/B ≤120 mm ² CSA AWM I A/B, II A/B, FT1 DESINA®
Design	based on VDE 0250
Conductor	extra fine wire strands of bare copper, acc. to IEC 60228 resp. VDE 0295, min. Class 6
Core insulation	PVC compound (UL/CSA 90°C rating)
Screen	braid of tinned copper wires, coverage 85% (nominal value)
Core identification	BK or GN/YE
Sheath	PVC compound (UL/CSA 90°C rating); colour: Orange, similar RAL 2003

Electrical properties at 20 °C

Nominal voltage U ₀ /U	IEC	600 / 1000 V
	UL/CSA	600 V
Test voltage		4000 V AC
Specific insulation resistance		> 20 G Ω x cm

Mechanical and thermal properties

Min. bending radius	flexing:	7,5 x cable diameter
	fixed installation:	3 x cable diameter
Temperature range	flexing:	-5 °C up to +90 °C (UL/CSA) max. conductor temp.
	fixed installation:	-40 °C up to +90 °C (UL/CSA) max. conductor temp.
Oil resistance	acc. to IEC 60811 bzw. VDE 0473-811 (90 °C, 7d)	
	80°C rating acc. to UL 758; CSA C22.2 No.210-05	
Flammability	flame retardant in acc. with IEC 60332-1-2 resp. VDE 0482-332-1-2	
	UL: Vertical flame test VW-1	
	CSA: FT1; FT2	
Tests	acc. to IEC 60811 resp. VDE 0473-811 and VDE 0472, EN 50395, EN 50396	
EC Directives	These cables are conform to the EC-Directives 2006/95/EC (Low Voltage Directive) and 2002/95/EC and 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances).	